GALAXIS

— 02729.HK —



Side Case Robot

- Ultra-High Efficiency
- Continuous Operation
- Operational Safety
- Easy Maintenance

Side Case Robot Product Specifications



Maximum travel speed 3 m/s



Aisle width only 850 mm



200 totes/hour (in/out)

Specification	6040DD	8060SD	6060DD
Fork type	Clamp fork	Clamp fork	Lift fork
Storage depth	Double-deep	Single-deep	Double-deep
Max. equipment height	12m	12m	12m
Min. pickup height	400mm	400mm	400mm
Max. cargo size	600*400mm	800*600mm	600*600mm
Max. Payload	50Kg	50Kg	50Kg
Max. lifting speed	3m/s	3m/s	3m/s
Max. travel speed	3m/s	3m/s	3m/s
Lifting positioning accuracy	±2mm	±2mm	±2mm
Travel positioning accuracy	±2mm	±2mm	±2mm
Power Supply	Sliding contact	Sliding contact	Sliding contact
Charging Voltage	380V/48V	380V/48V	380V/48V
Input frequency	50Hz	50Hz	50Hz
Ambient Temperature Range	-10℃~45℃	-10℃~45℃	-10℃~45℃
Min. Rack Level Pitch	350mm	350mm	/

ZHEJIANG GALAXIS TECHNOLOGY GROUP CO., LTD.
No.1118, Chicheng Road, Daqiao Town,Nanhu District, Jiaxing City, Zhejiang Province, China

T: 400-101-0947
E: info@galaxis-tech.com
w: www.galaxis-tech.com